



M5U 030/300 G3

**Brinell
universal hardness
testing machines
of the 3rd generation**

EMCO-TEST
YOUR FACTOR OF SAFETY.

Basic machine:

Macro-universal hardness tester for standardized test methods such as Brinell, EN ISO 6506 / ASTM E10 • Vickers, EN ISO 6507 / ASTM E92 • Rockwell, EN ISO 6508 / ASTM E18.

Brinell and Vickers indentations can be easily measured by means of an incremental linear scale.

Automatic focussing.

Testing load ranges: 196 – 29400N

Machine body made of cast iron and ergonomically designed.

Test anvil movement via hand wheel (M5U 030) or motor-driven test anvil (M5U 300).

Electronic test forces via load cell, closed loop and machine software.

Selection of the test method, tolerance limits and testing cycle time via LCD operating surface with touch screen.

Objectives and indenters at the motor-driven swivelling body can be changed manually.

Conversion of hardness values according to DIN EN ISO 18265.

The software includes extensive data management (import/ export function) and statistics functions.

With the new generation of M5U hardness testing machines even the occasional testing of components is made very easy.

Advantages of the 3rd generation:

- Very easy to operate by optimum user guidance and self-explanatory menus.
- Easy selection of all settings via drop-down menus.
- The hardness tester automatically saves test parameters and test results.
- Clearly structured data management with efficient import and export functions.
- Report forms ready for printing via USB interface.
- Possibility to select user groups with different authorizations.
- Connection to company network or internet with built-in network card.

Technical data:

TFT LCD monitor 6.2“, 150 x 60 mm, 640 x 240 pixel

Operation via touch screen with large and clearly arranged operating elements

Matt screen to display the test indentation (e.g. Vickers, Brinell), lighting by halogen lamp.

2 USB interfaces and 1 RJ45 100 MBit interface (Ethernet) for the data transfer to PC or network.

Possibility to connect an A4 printer to the USB interface to print A4 reports(direct printout from the hardness testing machine with necessity for an additional PC).

Objectives with magnifications: 15x / 35x / 82x / 140x

Testing height and mount capacity: maximum 415 mm testing height – M5U 030 maximum 280 mm mount capacity – both types
 maximum 500 mm testing height – M5U 300

Power supply: 240 V / 50/60 Hz
 110 V / 50/60 Hz

EMCO-TEST Prüfmaschinen GmbH

A-5431 Kuchl-Salzburg/Austria

Brennhoflehen-Kellau 174

Telefon +43 62 44 20 4 38, Fax +43 62 44 20 4 38-8

E-Mail: office@emcotest.com, www.emcotest.com

